





www.metsell.com info@metsell.com

+8801712 576914, +1508 762 8784, +971 54 592 6591, +86 13761376981



ABOUT US

Welcome to METSELL!

At METSELL, we are dedicated to providing high-quality solutions for the metal processing industry. With years of expertise, we specialize in supplying a comprehensive range of products, including Sink and Stabilizing Rolls, Hearth Rolls, Canalloy products, parts for galvanizing lines, and specialized bushes for Sink and Stabilizer Rolls.

Our commitment to excellence drives us to source and deliver only the best materials and components, ensuring optimal performance and longevity for your operations. We understand the critical role our products play in your manufacturing processes, and we strive to exceed your expectations with every order.

Our team of knowledgeable professionals is passionate about customer service, ready to assist you in finding the right solutions tailored to your specific needs. We pride ourselves on building strong, lasting relationships with our clients, empowering them to achieve their goals with the support of our innovative products.

At METSELL, we believe in continuous improvement and staying ahead of industry trends. This dedication allows us to provide cutting-edge solutions that enhance productivity and efficiency.

Partner with METSELL for reliable products and exceptional service. Together, let's drive your success in the metal processing industry!



SINK ROLL AND STABILIZING ROLL

Sink roll and Stabilizer roll are the important components in CGL lines. They are widely used in galvanizing.

Sink roll and stabilizer roll chemical compositions are as follows:

SL. No.	Element	Chemical Composition
1	C	≤ 0.03%
2	P	≤ 0.025%
3	Ni	13.0% - 15%
4	Mn	1.50% - 2.00%
5	S	≤ 0.03%
6	Mo	2.0 - 2.25%
7	Si	0.50% - 1.00%
8	Cr	16.0% - 18.0%



- Single sink roll total working life: 110-130 days.
- Sink roll barrel wall thickness: 19-50 mm.
- The surface of the sink roll barrels are grooved or drilling holes.
- Adding 4-5% chromium nitride and 1% rare earth elements to the molten metal before casting.
- Heat treatment will be done after roll semi-finished machining before finish machining.
- Heating 10 to 12 hours to make sink roll temperature increased into 1050 °C. To keep sink roll temperature at 1050°C constantly not less than 3 hours, then quench hardening by water.









HEARTH ROLL

Hearth Roll Chemical Composition As Below:

Description	Metarials					
HEARTH ROLL	Cr33Ni50w17 Cr25Ni35					

Roll Berrel Metarials Cr33Ni50W17 Chemical Composition As Below (%):

C Si		Mn	s	P	Cr	Ni	W	
0.15-0.25	≤ 0.3	≤ 0.3	≤ 0.04	€ 0.04	32.0 - 34.0	48.0 - 52.0	15-17	


Roll shaft and Journal Metarials is Cr25Ni35, Chemical Composition As Below (5):

Steel Grade	Metarials
GX40CrNiSiNb35-25	DIN Nr.1.4852

Composition As Below (%):

C	Si	Mn	P	s	Cr	Ni	Balance	
0.3-0.5	1.0 - 2.5	≤ 1.5	≤ 0.035	≤ 0.035	24.0 - 26.0	34.0 - 36.0	0.8 - 1.8	





Canalloy Products for Hot Dip Galvanizing Line

Chemical Compositions%									Physical properties at Room Temperature			
Grade	C	Mn	Si	Cr	Ni	Mo	W	Co	Fe	Other	Density g/cm3	Harness HRC
Stellite 4	0.80-1.20	1.00	1.00	28.0-32.0	3.00	1.50	12.5-15.5	Bal.	3.00	P.03Max S.03Max	8.56	40 - 50
Stellite 6	0.90-1.40	1.00	1.50	27.0-31.0	3.00	1.50	3.50-5.50	Bal.	3.00	P.03Max S.03Max	8.40	38 - 44
Stellite 12	1.10-1.70	1,00	1.00	28.0-32.0	3.00		7.00-9.50	Bal.	3.00	P.03Max S.03Max	8.40	44 - 49
Triballoy T800	≤0.1	-	≪3.5	16.5-18.5	*:	27.5-29.5	-	Bal.	-	P.03Max S.03Max	8.50	54 - 62



Bush for Sink Roll



Sleeve for Sink Roll







Stop





Threaded Rods






Customized Parts of Galvanizing Line







T800 Bushes for Sink Roll & Stabilizer Roll







Miscellaneous Rolls for Processing Lines of Steel Industry



Briddle Rolls with Tungsten Carbide




Briddle Rolls with Tungsten Carbide





Hypalon Coated Roll



Defector Roll







info@metsell.com



www.metsell.com



+880 1712 576914, +1508 762 8784, +971 54 592 6591, +86 13761376981

